

SAFETY DATA SHEET

Version 8.1
Revision Date 2022/08/25
Print Date 2025/08/12
Date of first issue 28.10.2021
SDS No. Eternal-Element - EY-TbM-202501
Product Number Eternal-Element - EY-TbM-202501

Terbium

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Terbium

Product Number : EY-TbM-202501

Brand : Eternal-Element

CAS-No. : 7440-27-9

1.2 Details of the supplier of the safety data sheet

Company : Shanghai Sheeny Metal Materials Co.,Ltd.

Room 210, Kedi Building,

No. 688 Huajiang Road, Jiading District,

SHANGHAI

201800 SHANGHAI CHINA

上海斯年金属材料有限公司

上海市嘉定区华江公路688号凯迪大厦210室

邮政编码：201800

Telephone : +86 16602150044

Fax : +86 16602150044

1.3 Emergency telephone

Emergency Phone # : +86 4006632276

1.4 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : For R&D use only. Not for pharmaceutical, household or other uses.

SECTION 2: Hazards identification

Summary of emergency

Page 1 of 10

powder gray Flammable solid., Self-heating; may catch fire., Causes skin irritation., Causes serious eye irritation., May cause long lasting harmful effects to aquatic life. Show this material safety data sheet to the doctor in attendance. After inhalation: fresh air. In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. After eye contact: rinse out with plenty of water., Call in ophthalmologist., Remove contact lenses. After swallowing: immediately make victim drink water (two glasses at most)., Consult a physician. Combustible. Development of hazardous combustion gases or vapours possible in the event of fire.

2.1 GHS Classification

Flammable solids (Category 2), H228

Self-heating substances and mixtures (Category 1), H251

Skin corrosion/irritation (Category 2), H315

Serious eye damage/eye irritation (Category 2A), H319

Long-term (chronic) aquatic hazard (Category 4), H413

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal Word

Danger

Hazard statement(s)

H228 Flammable solid.

H251 Self-heating; may catch fire.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H413 May cause long lasting harmful effects to aquatic life.

Precautionary statement(s)

Prevention

P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.

P235 + P410 Keep cool. Protect from sunlight.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P264 Wash skin thoroughly after handling.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

Response

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

If skin irritation occurs: Get medical advice/ attention.

If eye irritation persists: Get medical advice/ attention.

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage

P403 + P235 Store in a well-ventilated place. Keep cool.

P407 Maintain air gap between stacks/ pallets.

P420 Store away from other materials.

Disposal
P501

Dispose of contents/ container to an approved waste disposal plant.

2.3 Physical and chemical hazards

H228 Flammable solid.

H251 Self-heating; may catch fire.

2.4 Health hazards

H315 Causes skin irritation.
H319 Causes serious eye irritation.

2.5 Environmental hazards

H413 May cause long lasting harmful effects to aquatic life.

2.6 Other hazards - none

SECTION 3: Composition/information on ingredients

Substance / Mixture : Substance

3.1 Substances

Molecular weight : 158.93 g/mol
CAS-No. : 7440-27-9

Hazardous ingredients

Component	Classification	Concentration
Terbium powder	Flammable solids Category 2; Self-heating substances and mixtures Category 1; Skin corrosion/irritation Category 2; Serious eye damage/eye irritation Category 2A; Long-term (chronic) aquatic hazard Category 4; H228, H251, H315, H319, H413	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

4.4 Notes to physician

No data available

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing media**

Water Foam Carbon dioxide (CO₂) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Nature of decomposition products not known.

Combustible.

Development of hazardous combustion gases or vapours possible in the event of fire.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Advice for non-emergency personnel: Avoid inhalation of dusts. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up dry. Dispose of properly. Clean up affected area. Avoid generation of dusts.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed. Keep away from heat and sources of ignition.

Storage class

Storage class (TRGS 510) : 4.2 : Pyrophoric and self-heating hazardous materials

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material : Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time : 480 min

Material tested: KCL 741 Dermatril® L

Splash contact

Material : Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time : 480 min

Material tested: KCL 741 Dermatril® L

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

required when dusts are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

a)	Physical state	powder
b)	Color	gray
c)	Odor	No data available
d)	Melting point/freezing point	Melting point: 1,356 °C
e)	Initial boiling point and boiling range	255 °C
f)	Flammability (solid, gas)	The substance or mixture is a flammable solid with the category 2.
g)	Upper/lower flammability or explosive limits	No data available
h)	Flash point	Not applicable
i)	Autoignition temperature	Self-heating; may catch fire.
j)	Decomposition temperature	No data available
k)	pH	No data available
l)	Viscosity	Viscosity, kinematic: No data available Viscosity, dynamic: No data available
m)	Water solubility	0.1 g/l - Regulation (EC) No. 440/2008, Annex, A.6
n)	Partition coefficient: n-octanol/water	Not applicable for inorganic substances
o)	Vapor pressure	No data available
p)	Density	8.234 g/cm ³
	Relative density	No data available
q)	Relative vapor density	No data available
r)	Particle characteristics	No data available

- s) Explosive properties No data available
- t) Oxidizing properties none

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.2 Possibility of hazardous reactions

No data available

10.3 Conditions to avoid

no information available

10.4 Incompatible materials

Halogens, Strong acids

10.5 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Oral : No data available

Inhalation : No data available

Dermal : No data available

Skin corrosion/irritation

Causes skin irritation. (ECHA)

Serious eye damage/eye irritation

Causes serious eye irritation. (ECHA)

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

and emergency leaking installations. If transporting by road, please go along the specified route.

14.7 Incompatible materials

Halogens, Strong acids

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

Measures on the Environmental Administration of New Chemical Substances Registration

Registration/Notification number :

B1A222214260

Downstream users need to comply with the conditions of safe use of the chemical, understand the environmental and health hazard and risk management measures identified on the SDS as well as the local/national regulations concerning the chemical.

Other regulations

Please pay attention on the waste treatment should also comply with local regulations requirement.

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3.

H228	Flammable solid.
H251	Self-heating; may catch fire.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H413	May cause long lasting harmful effects to aquatic life.

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Eternal-Element Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www. eternal-element.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright Shanghai Sheeny Metal Mateirals Co.,Ltd. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the

information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact sales@eternal-element.com.